

## 4inch - 2in1 Downlight spec

Item No. FX-DL4-10W-DIM-5CC-#C

		<b>4inch - 2in1 Downlight spec</b>		
		Item No. FX-DL4-10W-DIM-5CC-#C		
市场信息 (Market Info.)	目标市场 (Target Market)	USA		
	系列 (Series)	Downlight		
	品名 (Item)	4inch 2in1 Downlight		
	图片 (Picture)			
电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz		
	标称功率W (Rated Power)	10W		
	功率因数 (Power Factor)	≥0.90		
	调光要求方式 (Dim Mode)	YES		
	调光兼容性 (Dim Compatible)	10-100%		
	光性能 (Light)	总光通量lm (Lumen output)	800LM	
		光效 lm/w (Lumen Efficacy)	≥80 lm/W	
		角度° (Beam Angle)	130°	
		色坐标中心 (Centre Point)		
		色温K (CCT)	2.7K,3K,3.5K,4K,5K	
显色指数 (Ra)		≥90		
色容差 (SDCM)		≤7		
特殊要求 (Special Spec)	/			
结构 (Mechanics)	产品尺寸mm (Dimension)	<b>φ132mm/ 5.2 inch</b>		
	开孔尺寸mm (Dimension)	<b>4.25inch/108mm</b>		
	输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved		
	串接方式	/		
	安装方式 (Mounting)	Recessed/ Retrofit		
	配件 (Accessories)	E26灯头*1PCS ( E26 base adapter * 1pc ) 防火桶卡簧*2PCS ( Torsion Springs * 2pcs ) 开孔安装卡簧*2PCS ( Spring Clips * 2pcs ) 接线帽*3PCS ( wire nuts * 3pcs ) 配件支架*2 ( bracket * 2pcs )		
	外观要求 (Appearance)	Color: White Material: Iron 扩散板 ( diffuser plate ): PS		
性能指标 (SPEC)	LM 80报告 (LM 80 Report)	YES		
	寿命判定 (Life Judgement)			
	整灯性能 (Whole Lamp)	L70寿命h (Lifetime)	30,000 hours	
		质保 (Warranty)	3years	
		噪音 (Noise)	< 24db	
		RoHS	Not Required	
		浪涌V (Surge)	2500V	
		绝缘耐压V (Voltage Resistance)	1000V 60s or 1200V 1s	
		使用温度 (Operating Temperature)	-20℃~40℃	
		存储温度 (Storage Temperature)	-20℃~60℃	
	特殊要求 (Special Spec)	Indoor only & Damp		
	认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)	
		能效认证 (Energy Efficacy)	YES	
		安规认证 (Safety)	UL/ETL (UL153,UL8750)	
		加州T24认证	YES	
气密性认证 (Air Tight)		YES		
电磁兼容 (EMC)	FCC			