


4inch - Retrofit Downlight spec				
市场信息 (Market Info.)	目标市场 (Target Market)	USA		
	系列 (Series)	Retrofit Downlight		
	品名 (Item)	4inch - Retrofit Downlight		
	图片 (Picture)			
性能指标 (SPEC)	电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz	
		标称功率W (Rated Power)	10W	
		功率因数 (Power Factor)	≥0.90	
		调光要求方式 (Dim Mode)	YES	
		调光兼容性 (Dim Compatible)	10-100%	
	光性能 (Light)	总光通量lm (Lumen output)	700 lm	
		光效 lm/w (Lumen Efficacy)	70 lm/W	
		角度° (Beam Angle)		
		色坐标中心 (Centre Point)	/	
		色温K (CCT)	2.7K,3K,3.5K,4K,5K	
		显色指数 (Ra)	≥90	
		色容差 (SDCM)	≤7	
	特殊要求 (Special Spec)	/		
	结构 (Mechanics)	产品尺寸mm (Dimension)	φ129mmx 63.5 mm	
		开孔尺寸mm (Dimension)		
		输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved	
		串接方式	/	
		安装方式 (Mounting)	Retrofit	
		配件 (Accessories)	TP24 Supply wire adapter*1PC Wire caps*3PCS	
		外观要求 (Appearance)	Color: white Material: Metal + PC	
	整灯性能 (Whole Lamp)	LM 80报告 (LM 80 Report)	YES	
		寿命判定 (Life Judgement)	/	
		L70寿命h (Lifetime)	50,000 hours	
		质保 (Warranty)	5 year	
		噪音 (Noise)	<24db	
RoHS		Not Required		
浪涌V (Surge)		2500V		
绝缘耐压V (Voltage Resistance)		1000V 60s or 1200V 1s		
使用温度 (Operating Temperature)		-20℃-40℃		
存储温度 (Storage Temperature)		-20℃-60℃		
特殊要求 (Special Spec)		Indoor only & Damp		
认证 (Certification)		环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)	
		能效认证 (Energy Efficacy)	YES	
		安规认证 (Safety)	UL/ETL (UL153,UL8750)	
		加州T24认证	YES	
	气密性认证 (Air Tight)	No		
电磁兼容 (EMC)	FCC			