

5/6inch - 3in1 Frameless Downlight spec				
市场信息 (Market Info.)	目标市场 (Target Market)	USA		
	系列 (Series)	3in1 Frameless Downlight		
	品名 (Item)	5/6inch-3in1 Frameless Downlight		
	图片 (Picture)			
电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz		
	标称功率W (Rated Power)	12W±10%		
	功率因数 (Power Factor)	≥0.90		
	调光要求方式 (Dim Mode)	YES		
	调光兼容性 (Dim Compatible)	10-100%		
	光性能 (Light)	总光通量lm (Lumen output)	1000 lm	
		光效lm/w (Lumen Efficacy)	≥70 lm/W	
		角度° (Beam Angle)		
		色坐标中心 (Centre Point)	/	
		色温K (CCT)	2.7K,3K,3.5K,4K,5K	
显色指数 (Ra)		≥90		
色容差 (SDCM)		≤6		
特殊要求 (Special Spec)	/			
性能指标 (SPEC)	产品尺寸mm (Dimension)	φ183mmx 82 mm/ 7.20*3.23 inch		
	开孔尺寸mm (Dimension)	5.25inch/133mm - 6.25inch/159mm		
	输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved		
	串接方式	/		
	安装方式 (Mounting)	Flush mount/ Recessed/ Retrofit		
	配件 (Accessories)	Mounting Bracket*1PC Spring Clips*2PCS Torsion Springs*2PCS E26 Base Aadpter*1PCS TP24 Supply Wire Adapter*1PC Wiring Cap*3PCS M3*3 Screw 3PCS; #8-32-1-1/2 Screw*2PCS; #8-32-3/4 Screw*2PCS;		
	外观要求 (Appearance)	Color: white Material: Matel + PC		
整灯性能 (Whole Lamp)	LM 80报告 (LM 80 Report)	YES		
	寿命判定 (Life Judgement)	/		
	L70寿命h (Lifetime)	50,000 hours		
	质保 (Warranty)	5 year		
	噪音 (Noise)	<24db		
	RoHS	Not Required		
	浪涌V (Surge)	2500V		
	绝缘耐压V (Voltage Resistance)	1000V 60s or 1200V 1s		
	使用温度 (Operating Temperature)	-20℃-40℃		
	存储温度 (Storage Temperature)	-20℃-60℃		
特殊要求 (Special Spec)	Indoor only & Damp			
认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)		
	能效认证 (Energy Efficacy)	YES		
	安规认证 (Safety)	UL/ETL (UL153,UL8750)		
	加州T20认证	YES		
	气密性认证 (Air Tight)	YES		
电磁兼容 (EMC)	FCC			