

5/6inch - 3in1 Narrow Downlight spec			
市场信息 (Market Info.)	目标市场 (Target Market)	USA	
	系列 (Series)	3in1 Narrow Downlight	
	品名 (Item)	5/6inch-3in1 Narrow Downlight	
	图片 (Picture)		
性能指标 (SPEC)	电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz
		标称功率W (Rated Power)	12±10%
		功率因数 (Power Factor)	≥0.90
		调光要求方式 (Dim Mode)	YES
		调光兼容性 (Dim Compatible)	10-100%
	光性能 (Light)	总光通量lm (Lumen output)	850 lm
		光效 lm/w (Lumen Efficacy)	≥70 LM/W
		角度° (Beam Angle)	110°
		色坐标中心 (Centre Point)	
		色温K (CCT)	2.7K,3K,3.5K,4K,5K
		显色指数 (Ra)	≥90
		色容差 (SDCM)	≤6
		特殊要求 (Special Spec)	/
	结构 (Mechanics)	产品尺寸mm (Dimension)	φ183mmx65mm/ 7.20*2.56 inch
		开孔尺寸mm (Dimension)	6.3inch/160mm
		输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved
		串接方式	/
		安装方式 (Mounting)	Flush mount/ Recessed/ Retrofit
		配件 (Accessories)	Mounting Bracket*1PC Spring Clips*2PCS Torsion Springs*2PCS E26 Base Aadpter*1PCS TP24 Supply Wire Adapter*1PC Wiring Cap*3PCS M3*3 Screw 3PCS; #8-32-1-1/2 Screw*2PCS; #8-32-3/4 Screw*2PCS;
		外观要求 (Appearance)	Color: white Metarial: Matel + PC Diffuser Plate: PP
整灯性能 (Whole Lamp)	LM 80报告 (LM 80 Report)	YES	
	寿命判定 (Life Judgement)		
	L70寿命h (Lifetime)	50,000 hours	
	质保 (Warranty)	5 year	
	噪音 (Noise)	<24db	
	RoHS	Not Required	
	浪涌V (Surge)	2500V	
	绝缘耐压V (Voltage Resistance)	1000V 60s or 1200V 1s	
	使用温度 (Operating Temperature)	-20℃~40℃	
	存储温度 (Storage Temperature)	-20℃~60℃	
	特殊要求 (Special Spec)	Indoor only & Damp	
	认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)
能效认证 (Energy Efficacy)		YES	
安规认证 (Safety)		UL/ETL (UL153,UL8750)	
加州T20认证		YES	
气密性认证 (Air Tight)		YES	
电磁兼容 (EMC)		FCC	