

8inch - 3in1 Narrow Downlight spec			
市场信息 (Market Info.)	目标市场 (Target Market)	USA	
	系列 (Series)	3in1 Narrow Downlight	
	品名 (Item)	8inch-3in1 Narrow Downlight	
	图片 (Picture)		
电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz	
	标称功率W (Rated Power)	18±10%	
	功率因数 (Power Factor)	≥0.90	
	调光要求方式 (Dim Mode)	YES	
	调光兼容性 (Dim Compatible)	10-100%	
	光性能 (Light)	总光通量lm (Lumen output)	稳态≥1200 lm
		光效lm/w (Lumen Efficacy)	≥70 lm/W
		角度° (Beam Angle)	110°
		色坐标中心 (Centre Point)	
		色温K (CCT)	2.7K,3K,3.5K,4K,5K
显色指数 (Ra)		≥90	
色容差 (SDCM)		≤6	
特殊要求 (Special Spec)	/		
性能指标 (SPEC)	产品尺寸mm (Dimension)	φ225 mmx 65mm/ 8.86*2.56 inch	
	开孔尺寸mm (Dimension)	6.3inch/160mm	
	输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved	
	串接方式	/	
	安装方式 (Mounting)	Flush mount/ Recessed/ Retrofit	
	配件 (Accessories)	Mounting Bracket*1PC Spring Clips*2PCS Torsion Springs*2PCS E26 Base Aadpter*1PCS TP24 Supply Wire Adapter*1PC Wiring Cap*3PCS M3*3 Screw 3PCS; #8-32-1-1/2 Screw*2PCS; #8-32-3/4 Screw*2PCS;	
	外观要求 (Appearance)	Color: white Metarial: Matel + PC Diffuser Plate: PP	
	LM 80报告 (LM 80 Report)	YES	
	寿命判定 (Life Judgement)		
	整灯性能 (Whole Lamp)	L70寿命h (Lifetime)	50,000 hours
质保 (Warranty)		5 year	
噪音 (Noise)		<24db	
RoHS		Not Required	
浪涌V (Surge)		2500V	
绝缘耐压V (Voltage Resistance)		1000V 60s or 1200V 1s	
使用温度 (Operating Temperature)		-20℃-40℃	
存储温度 (Storage Temperature)		-20℃-60℃	
特殊要求 (Special Spec)	Indoor only & Damp		
认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)	
	能效认证 (Energy Efficacy)	YES	
	安规认证 (Safety)	UL/ETL (UL153,UL8750)	
	加州T20认证	YES	
	气密性认证 (Air Tight)	YES	
	电磁兼容 (EMC)	FCC	