


5/6inch - 2in1 Baffle Downlight spec				
市场信息 (Market Info.)	目标市场 (Target Market)	USA		
	系列 (Series)	2in1 Baffle Downlight		
	品名 (Item)	5/6inch-2in1 Baffle Downlight		
	图片 (Picture)			
性能指标 (SPEC)	电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz	
		标称功率W (Rated Power)	12W	
		功率因数 (Power Factor)	≥0.90	
		调光要求\方式 (Dim Mode)	YES/Traic	
		调光兼容性 (Dim Compatible)	10-100%	
	光性能 (Light)	总光通量 lm (Lumen output)	850 lm	
		光效 lm/w (Lumen Efficacy)	≥65 lm/W	
		角度 ° (Beam Angle)	110°	
		色坐标中心 (Centre Point)	/	
		色温K (CCT)	2. 7K, 3K, 4K, 5K	
		显色指数 (Ra)	≥80	
		色容差 (SDCM)	≤7	
	特殊要求 (Special Spec)	/		
	结构 (Mechanics)	产品尺寸mm (Dimension)	φ183mmx 102 mm	
		开孔尺寸mm (Dimension)	160mm	
输入线规格 (Input Wire SPEC)		American standard three core wire ETL/UL approved		
串接方式		/		
安装方式 (Mounting)		Recessed/ Retrofit		
配件 (Accessories)		配防火桶安装弹簧卡扣*2PCS ( Torsion Springs * 2pcs ) E26转换灯头*1PC( E26 base adapter * 1pc ) 带TP24接头连接线*1PC( TP24 Supply wire adapter*1PC) 接线帽*3PCS (Wire nuts*3PCS)		
外观要求 (Appearance)	Color: white Material: Metal + PC 扩散板 ( diffuser plate ): PS			
整灯性能 (Whole Lamp)	LM 80报告 (LM 80 Report)	YES		
	寿命判定 (Life Judgement)	/		
	L70寿命h (Lifetime)	50,000 hours		
	质保 (Warranty)	5 year		
	噪音 (Noise)	<24db		
	RoHS	Not Required		
	浪涌V (Surge)	1500V		
	绝缘耐压V (Voltage Resistance)	1000V 60s or 1200V 1s		
	使用温度 (Operating Temperature)	-20℃~40℃		
	存储温度 (Storage Temperature)	-20℃~60℃		
	特殊要求 (Special Spec)	Indoor only & Damp		
	认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)	
		能效认证 (Energy Efficacy)	YES	
安规认证 (Safety)		UL/ETL (UL153,UL8750)		
加州T24认证		NO		
气密性认证 (Air Tight)		YES		
电磁兼容 (EMC)		FCC		