


## 4inch - Slim Downlight spec

市场信息 (Market Info.)	目标市场 (Target Market)	USA	
	系列 (Series)	Slim Downlight	
	品名 (Item)	4inch-Slim Downlight	
	图片 (Picture)		
性能指标 (SPEC)	电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz
	标称功率W (Rated Power)	10W	
	功率因数 (Power Factor)	≥0.90	
	调光要求\方式 (Dim Mode)	YES	
	调光兼容性 (Dim Compatible)	10-100%	
	光性能 (Light)	总光通量 lm (Lumen output)	650LM
	光效 lm/w (Lumen Efficacy)	≥60 lm/W	
	角度 ° (Beam Angle)	110°	
	色坐标中心 (Centre Point)		
	色温K (CCT)	2.7K,3K,4K,5K	
	显色指数 (Ra)	≥80	
	色容差 (SDCM)	≤7	
	特殊要求 (Special Spec)	/	
	结构 (Mechanics)	产品尺寸mm (Dimension)	φ120mm
	开孔尺寸mm (Dimension)	4.25inch / φ110mm	
	输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved	
	串接方式	/	
	安装方式 (Mounting)	Recessed	
	配件 (Accessories)	Wire Nuts*3PCS	
	外观要求 (Appearance)	Color: white Material: Metal	
		LM 80报告 (LM 80 Report)	YES
		寿命判定 (Life Judgement)	
	整灯性能 (Whole Lamp)	L70寿命h (Lifetime)	50,000 hours
	质保 (Warranty)	5 year	
	噪音 (Noise)	<24db	
RoHS	Not Required		
浪涌V (Surge)	2500V		
绝缘耐压V (Voltage Resistance)	1000V 60s or 1200V 1s		
使用温度 (Operating Temperature)	-20℃~40℃		
存储温度 (Storage Temperature)	-20℃~60℃		
特殊要求 (Special Spec)	Indoor only & Damp		
认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)	
能效认证 (Energy Efficacy)	YES		
安规认证 (Safety)	UL/ETL (UL153,UL8750)		
加州T24认证	No		
气密性认证 (Air Tight)	YES		
电磁兼容 (EMC)	FCC		