

4inch - Slim Downlight spec

| | | | | |
|-------------------------|------------------------------|--|-----------------------------|--|
| | | 4inch - Slim Downlight spec | | |
| 市场信息 (Market Info.) | 目标市场 (Target Market) | USA | | |
| | 系列 (Series) | Slim Downlight | | |
| | 品名 (Item) | 4inch-Slim Downlight | | |
| | 图片 (Picture) |  | | |
| 性能指标 (SPEC) | 电性能 (Electronics) | 额定电压V (Input Voltage) | 120V 60Hz | |
| | | 标称功率W (Rated Power) | 10W | |
| | | 功率因数 (Power Factor) | ≥0.90 | |
| | | 调光要求\方式 (Dim Mode) | YES | |
| | | 调光兼容性 (Dim Compatible) | 10-100% | |
| | 光性能 (Light) | 总光通量 lm (Lumen output) | 650LM | |
| | | 光效 lm/w (Lumen Efficacy) | ≥60 lm/W | |
| | | 角度 ° (Beam Angle) | 110° | |
| | | 色坐标中心 (Centre Point) | | |
| | | 色温K (CCT) | 2.7K,3K,3.5K,4K,5K | |
| | | 显色指数 (Ra) | ≥80 | |
| | | 色容差 (SDCM) | ≤7 | |
| | | 特殊要求 (Special Spec) | / | |
| | 结构 (Mechanics) | 产品尺寸mm (Dimension) | φ120mm | |
| | | 开孔尺寸mm (Dimension) | 4.25inch / φ110mm | |
| 输入线规格 (Input Wire SPEC) | | American standard three core wire ETL/UL approved | | |
| 串接方式 | | / | | |
| 安装方式 (Mounting) | | Recessed | | |
| 配件 (Accessories) | | Wire Nuts*3PCS | | |
| 外观要求 (Appearance) | | Color: white Metarial: Matel | | |
| 整灯性能 (Whole Lamp) | LM 80报告 (LM 80 Report) | YES | | |
| | 寿命判定 (Life Judgement) | | | |
| | L70寿命h (Lifetime) | 50,000 hours | | |
| | 质保 (Warranty) | 5 year | | |
| | 噪音 (Noise) | <24db | | |
| | RoHS | Not Required | | |
| | 浪涌V (Surge) | 2500V | | |
| | 绝缘耐压V (Voltage Resistance) | 1000V 60s or 1200V 1s | | |
| | 使用温度 (Operating Temperature) | -20℃~40℃ | | |
| | 存储温度 (Storage Temperature) | -20℃~60℃ | | |
| | 特殊要求 (Special Spec) | Indoor only & Damp | | |
| | 认证 (Certification) | 环保认证 (Chemical) | CA PROP65(LEAD/DEHP<100ppm) | |
| | | 能效认证 (Energy Efficacy) | YES | |
| | | 安规认证 (Safety) | UL/ETL (UL153,UL8750) | |
| | | 加州T24认证 | No | |
| 气密性认证 (Air Tight) | | YES | | |
| 电磁兼容 (EMC) | FCC | | | |