

## 6inch - Slim Downlight spec

市场信息 (Market Info.)	目标市场 (Target Market)	USA	
	系列 (Series)	Slim Downlight	
	品名 (Item)	6inch-Slim Downlight	
	图片 (Picture)		
性能指标 (SPEC)	电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz
		标称功率W (Rated Power)	12W
		功率因数 (Power Factor)	≥0.90
		调光要求\方式 (Dim Mode)	YES
		调光兼容性 (Dim Compatible)	10-100%
	光性能 (Light)	总光通量 lm (Lumen output)	850LM
		光效 lm/w (Lumen Efficacy)	≥70 lm/W
		角度 ° (Beam Angle)	110°
		色坐标中心 (Centre Point)	
		色温K (CCT)	2.7K,3K,3.5K,4K,5K
		显色指数 (Ra)	≥80
		色容差 (SDCM)	≤7
		特殊要求 (Special Spec)	/
	结构 (Mechanics)	产品尺寸mm (Dimension)	φ174mm
		开孔尺寸mm (Dimension)	6.25inch/160mm
		输入线规格 (Input Wire SPEC)	American standard three core wire ETL/UL approved
		串接方式	/
		安装方式 (Mounting)	Recessed
		配件 (Accessories)	Wire Nuts*3PCS
		外观要求 (Appearance)	Color: white Material: Metal
	整灯性能 (Whole Lamp)	LM 80报告 (LM 80 Report)	YES
		寿命判定 (Life Judgement)	
		L70寿命h (Lifetime)	50,000 hours
		质保 (Warranty)	5 years
		噪音 (Noise)	<24db
RoHS		Not Required	
浪涌V (Surge)		2500V	
绝缘耐压V (Voltage Resistance)		1000V 60s or 1200V 1s	
使用温度 (Operating Temperature)		-20℃~40℃	
存储温度 (Storage Temperature)		-20℃~60℃	
特殊要求 (Special Spec)		Indoor only & Damp	
认证 (Certification)		环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)
		能效认证 (Energy Efficacy)	YES
		安规认证 (Safety)	UL/ETL (UL153,UL8750)
		加州T24认证	NO
	气密性认证 (Air Tight)	YES	
	电磁兼容 (EMC)	FCC	