


6inch - Downlight spec

		6inch - Downlight spec		
市场信息 (Market Info.)	目标市场 (Target Market)	USA		
	系列 (Series)	RGBWCW Downlight		
	品名 (Item)	6inch Downlight		
	图片 (Picture)			
性能指标 (SPEC)	电性能 (Electronics)	额定电压V (Input Voltage)	120V 60Hz	
		标称功率W (Rated Power)	12W	
		功率因数 (Power Factor)	≥0.90	
		调光要求方式 (Dim Mode)	YES	
		调光兼容性 (Dim Compatible)	10-100%	
	光性能 (Light)	总光通量lm (Lumen output)	800LM	
		光效 lm/w (Lumen Efficacy)	≥65 lm/W	
		角度° (Beam Angle)	130°	
		色坐标中心 (Centre Point)		
		色温K (CCT)	RGB	
		显色指数 (Ra)	≥90	
		色容差 (SDCM)	≤7	
	特殊要求 (Special Spec)	/		
	结构 (Mechanics)	产品尺寸mm (Dimension)	φ174mm/ 6.85 inch	
		开孔尺寸mm (Dimension)	6.29inch/160mm	
输入线规格 (Input Wire SPEC)		American standard three core wire ETL/UL approved		
串接方式		/		
安装方式 (Mounting)		Recessed		
配件 (Accessories)		Spring*2PCS Wire caps*3PCS		
外观要求 (Appearance)		Color: White Material: Metal		
整灯性能 (Whole Lamp)	LM 80报告 (LM 80 Report)	YES		
	寿命判定 (Life Judgement)			
	L70寿命h (Lifetime)	50,000 hours		
	质保 (Warranty)	5years		
	噪音 (Noise)	<24db		
	RoHS	Not Required		
	浪涌V (Surge)	2500V		
	绝缘耐压V (Voltage Resistance)	1000V 60s or 1200V 1s		
	使用温度 (Operating Temperature)	-20℃~40℃		
	存储温度 (Storage Temperature)	-20℃~60℃		
	特殊要求 (Special Spec)	Indoor only & Damp		
	认证 (Certification)	环保认证 (Chemical)	CA PROP65(LEAD/DEHP<100ppm)	
		能效认证 (Energy Efficacy)	YES	
		安规认证 (Safety)	UL/ETL (UL153,UL8750)	
		加州T24认证	NO	
气密性认证 (Air Tight)		YES		
电磁兼容 (EMC)		NO		